

Sika® MultiSeal T

Bituminous sealing tape

Construction

Product Description Self-adhesive, bituminous sealing tape, one side laminated with aluminium foil.

Uses Sealing and repairing against water ingress and draughts in:

- Roofs including sheet metal work
- Building cracks
- Bituminous felts and other types of roofing sheet

Characteristics / Advantages

- Very easy to apply
- Very economical
- Good adhesion to many substrates
- Weather-proof
- Self-adhesive
- UV-resistant
- Bitumen-resistant
- Can be over-painted
- Can be applied at low temperatures

Product Data

Appearance / Colours

- Upper side: grey
- Lower side: Self-adhesive bituminous tape protected with a release film

Packaging

Length of roll	Width of roll	Rolls per box
3 m	100 mm	12
3 m	200 mm	6

Storage Conditions / Shelf-Life 24 months from date of production if stored in unopened, undamaged original sealed containers, in dry conditions and protected from direct sunlight at temperatures between +10°C and +30°C.

Chemical Base Modified bituminous tape

Density ~ 1.5 g/cm³ (+20°C)

Layer Thickness ~ 1.5 mm (total thickness)

Fire Rating B2 according to DIN 4100

Service Temperature -20°C to +85°C

Tensile Strength Longitudinally: ~ 1.6 N/mm²
Transversally: ~ 2.16 N/mm²

Elongation at Break 15 - 75%



System Information

Substrate Quality	The substrate must be sound, clean, dry and free from all surface contaminants.
Substrate Preparation	All loose particles, release agents, laitance, paint, rust and other poorly adhering materials must be removed by suitable hand or mechanical preparation techniques. Metallic substrates, plastics etc. have to be thoroughly cleaned with a solvent (e.g. Sika® Cleaner-205). On porous substrates (concrete, renderings, etc.) the adhesion can be improved with a bituminous primer (e.g. Inertol-1). Let the primer dry for at least 1 hour.
Substrate Temperature	+5°C min. / +45°C max. At temperatures below +10°C the tape and the substrate must be warmed up before and during the application. Use hot air equipment.
Ambient Temperature	+5°C min. / +45°C max. At temperatures below +10°C the tape and the substrate must be warmed before and during the application. Use hot air equipment.
Substrate Moisture Content	The substrate must be dry.
Application Method / Tools	Cut the tape to the necessary length, remove the release film and press the tape firmly onto the substrate with a suitable pressure roller. All joint connections have to be overlapped min. 50 mm. Note: Adhesion to the substrate can be increased by heating up the tape with a hot-air-dryer during the application.
Notes on Application / Limitations	Not suitable for sealing against water pressure. For waterproofing applications with water pressure, contact your local Sika Technical Service. Not suitable for overhead application with high temperature (> +25°C). Due to the bituminous content of the tape, coatings, plastics and natural stones may discolour. On porous substrates, water infiltration underneath the Sika® MultiSeal® is possible.
Value Base	All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.
Health and Safety Information	For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.
Legal Notes	The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Singapore Pte Ltd
200 Pandan Loop, 06-02 Pantech 21
Singapore 128388
SINGAPORE

Phone: +65 6777 2811
Fax: +65 6779 6200
e-mail: info@sq.sika.com
www.sika.com.sg



Sika Kimia Sdn Bhd
Lot 689 Nilai Industrial Estate
71800 Nilai, Negeri Sembilan DK
MALAYSIA

Phone: +606-7991762
Fax: +606-7991980
e-mail: info@my.sika.com
www.sika.com.my

