

Light Towers

The HiLight range. Your site, your light!

Authorized distributor

Metal Halide HiLight V4 to LED HiLight V5+

- The HardHat® range. Providing outstanding safety and efficiency.
- Perfect for multiple drop rental applications.
- Providing users a robust and easy-to-transport set of lighting options that match any site requirements.
- The extended safety features also guarantee the protection of bulbs during transportation.



Atlas Copco Light Tower		HiLight V4W	HiLight V4WK	HiLight V4+	HiLight V5+	HiLight V5+K
Type		Metal Halide	Metal Halide	LED	LED	LED
Wattage	W	4x1000			4x350	
Coverage	m²	4000 (20 Lux Average)			5000 (20 Lux Average)	
Mast Type		Vertical, Manual, 7.5m, 360° Rotation				
Extra Features		Hardhat, Canopy				
Operating Condition	°C	-20~50				
Voltage/Frequency		230V / 50Hz				
Wind Speed	km/h	80				
Construction		DOT US Compliant Unibody Trailer with 4-Point Levelling System				
Enclosure		Gull-wing Hardhat Doors				
Engine		Kubota	Kohler	Kubota	Kubota	Kohler
Model		D1105	KDW1003	Z482	Z482	KDW702
Rating @ 1500rpm	kW	8	8	2.7	2.7	5.5
External Tank	l(h)	160 (90h)	160 (95h)	110 (300h)	110 (150h)	110 (135h)
Engine Type		3 Cyl. Water-Cooled		2 Cyl. Water-Cooled		
Alternator		Atlas Copco			MeccAlte	
Type		DP06/AG164		ACA132B	LT3/75	
Rating	kVA	6		3	3.5	
Aux. Power Output	kW	2		1	1	
Dimensions						
L x W x H (In Transport, Fixed Towbar)	mm	1800 x 1350 x 2970			1670 x 1100 x 2500	
L x W x H (In Operation)	mm	2900 x 2310 x 7540			2900 x 2310 x 7540	
Dry Weight (Undercarriage Type)	kg	826			702	

Max ambient temperature at sea level is 49°C

Authorised Distributor: