

Rotary Screw Air Compressors

SSR®45-75kW / 75-100HP



SSR 45-75 kW / 75-100HP

Looking for a rugged, reliable and energy efficient air compressor? The Ingersoll-Rand SSR is for you. With our integral gear drive system, 8000-hour coolant, and leak-free design you can count on the SSR for years to come.

If your business demands any of these then check out the SSR:

- Reliability
- Ease of installation
- Accurate information
- Easy and low cost of maintenance
- Efficiency
- Quiet operation
- Flexible options



There's more to the picture

Providing air solutions is our specialty. We offer compressed air audits, system design assistance, and other services and products that maximize the efficiency of your entire plant air system.

LINK 1 – Air Compressor:

An air compressor is the first link in a chain that acts as a dependable supply of air to your plant. Shouldn't the strength of the other links matter?

LINK 2 – System components:

We offer a complete lineup of compressed air dryers, filters, Simlair distribution pipework and other accessories that work seamlessly with your SSR rotary compressor to provide the air quantity and quality you need.

LINK 3 – Service

Ingersoll-Rand is known worldwide for its extensive and highly reliable service organization. Factory certification to service SSRs is a rigorous process unmatched in the industry. Our worldwide distribution network knows what to do and how to do it.



LINK 4 –Manufacturer:

Ingersoll-Rand is the compressed air solutions global leader with well over 100 years of experience in the manufacture of compressed air products. We've earned our market-leading position through our commitment to the highest levels of customer service and product performance, reliability and quality.




Package design

- It's tough, quiet, and easy to service

Higher Ambient Rating – Can you afford a shutdown in the heat of summer? The SSR operates easily in ambient temperatures up to 115°F/46°C. Even if you're not in a sweltering climate, it ensures fewer nuisance shutdowns due to summer heat or dirty coolers.


Easy Installation – Set it down, hook it up to the proper electrical service and piping system, cover the forklift holes and let it go. No vibration mounts are required.

Quiet operation – A subassembly isolates the drive train from the package for virtually vibration free and quiet operation.



Superb Serviceability – Routine maintenance is done through one convenient latched panel on the front of the machine making machine servicing easier and quicker.

Tested as a Complete Package – Every SSR completes our state of the art computer based performance and operations test. This multi-point test ensures our rigid manufacturing quality standards have been met as well as trouble-free operation of the unit, beginning with the initial start-up at your facility.



The SSR Drive Train

There are many reasons that customers like you consistently give us high ratings for quality and reliability. The SSR drive train is certainly one of them. First used in the 1970s, the SSR drive train has proven itself over 100,000 times.


Superior Airend Design – At the heart of the SSR is our time-proven rotary screw airend, known for trouble free operation with minimal maintenance. All airends are designed and built in-house, guaranteeing critical quality control. The airends are built on technically advanced machinery that is generations ahead of what other manufacturers use. This ability to hold tolerances measured in microns increases the reliability and life of the airend. The airend is a robust design, built with premium materials.

Integral Gear Drive – It's the only drive system that is maintenance free and totally isolated from the environment.

The Dedicated Motor – Compressor motors are usually one of the hardest running motors in a plant. If your business depends on compressed air, then it depends on the quality and strength of the motor. The extra toughness designed and built into the SSR motor means it will run when other motors quit. Maintenance and repair on the SSR motor is just like any other motor you own.

Intellisys® – Total control at your fingertips.

The SSR comes standard with the Intellisys controller—the most advanced active microprocessor available on any compressor. First built into SSRs in the late 1980s, Intellisys has been updated to employ the latest technology, increasing the reliability while keeping it simple.






Simple use – You don’t need to be a computer guru or symbol reader to use the Intellisys controller. Information is displayed in clear, plain text and not in codes. Adjustments are easily made through the finger touch control panel and there are no pressure switches to drift or adjust.


More information, more accurate – Intellisys constantly monitors and displays exactly what’s happening in your SSR and displays it on the face panel. That same information can be sent via modem to your service provider for trending or it can be sent in a modbus protocol to your building control system.

Time saving diagnostics – The Intellisys monitors 11 key internal functions of the SSR. If any of those deviate from its preprogrammed limit, the controller will automatically warn and, if required, shutdown the compressor. The display then indicates the problem and the sequence of events leading to the shutdown. This feature reduces costly troubleshooting and minimizes downtime. Since Intellisys remembers what all operating parameters were prior to shutdown, the restarting process is a snap.




UltraCoolant – You’ll be surprised by the advantages of using UltraCoolant. First, UltraCoolant has a 2 year/8000 hour life. The coolant is changed less often, keeping maintenance costs to a minimum. Secondly, since UltraCoolant was designed specifically for rotary compressors, it assures uninterrupted service by lubricating, sealing, and cooling under all normal operating conditions. Third, UltraCoolant’s superior separating properties combined with our patented separator system means less coolant is passed downstream to your plant’s processes. Lower coolant carryover equals less cost for coolant make-up. Finally, UltraCoolant’s lack of hydrocarbons eliminates the chance of varnish formation. Varnish shortens separator life, coats rotors, bearings and heat exchangers (raising operating temperatures) and reduces airtight reliability.

Patented Separator Design – Our patented two stage conical baffle separator minimizes coolant carryover to your plant and reduces the amount of make-up replaced. This design also reduces the impact that overfilling or underfilling can have on coolant carryover.



Inherent Leak Free Design –


By reducing the number of fittings and using SAE O-ring fittings on all connections larger than 1/4" (6 mm), we’ve significantly reduced the potential leakage problem associated with conventional threaded connections and piping schemes.



Options and Accessories

Upper range modulation with Automatic Control Selector –

For those plants where the demand profile is high or storage is minimal, upper range modulation stabilizes plant air pressure, reducing cycling of components with a minimal power penalty. Automatic Control Selector uses the Intellisys’ built in intelligence to monitor air consumption and choose the appropriate control mode.



Remote start/stop – This option gives you offsite on/off control.

Star Delta Starting – A motor requires 600% of its full load amps to start. With star delta starting, the current used to start is only 200%, resulting in a cushioned start for both mechanical and electrical components (standard on 50Hz units).

Outdoor modification – Outdoor modification includes IP65 option and moves the package discharge from the top of the package to the side.

Heavy Duty filter – The heavy duty air filter is designed for applications where the heavy dust load would cause the air filter to plug early.

Alternate coolants – H1F food grade or diester-based SSR coolant are available.

Condensate Separator System (CSS) – Provides clean water disposal with minimal operating costs.

Intellisys System Controller (ISC) – Maintains system pressure while minimizing operating costs.

IP65 – For those applications where the compressor will be exposed to water.

Watercooled – SSRs can be outfitted with a variety of watercooled heat exchangers. The standard cooler is admiralty brass with options existing for 90/10 copper nickel, 70/30 copper nickel and stainless steel.

50Hz SSR 45-75kW Performance								
Nominal kW	Free Air Delivery - M ³ /min (1)				Length (mm)	Width (mm)	Height (mm)	Weight (kg)
	ML 7.5 barg	MM 8.5 barg	MH 10 barg	MJ 11.4 barg				
45	7.4	7.1	6.5	-	1689	1605	1696	953
55	10.1	9.1	8.3	7.6	1689	1605	1696	1270
75	13.0	12.1	11.0	10.2	1689	1605	1696	1315

60Hz SSR 75-100HP Performance								
Nominal HP	Free Air Delivery - CFM (1)				Length (in)	Width (in)	Height (in)	Weight (lbs)
	XF 100 psig	EP 125 psig	HP 140 psig	XP 165 psig				
75	386	332	299	248	67	63	67	2800
100	495	446	412	358	67	63	67	2900

(1) FAD (Free Air Delivery) CFM and M³/Min. are ratings of full package performance in accordance with CAGI-PNEUROP acceptance test standard PN2CPTC2 or ISO1217: 1996 Annex C.



Ingersoll Rand Industrial Technologies provides products, services and solutions that enhance our customers' energy efficiency, productivity and operations. Our diverse and innovative products range from complete compressed air systems, tools and pumps to material and fluid handling systems. We also enhance productivity through solutions created by Club Car®, the global leader in golf and utility vehicles for businesses and individuals.

Authorised Distributor:



Pansar Company Sdn. Bhd. 196501000061 (50977M)

Wisma Pansar, 23-27 Jalan Bengkel, P.O.Box 319, 96007 Sibul, Sarawak.

T +6084-333 366 **F** +6084-314 555 **E** marine.industrial@pansar.com.my **AW** pansar.com.my

Kuala Lumpur Regional Office

No. 7 Jalan Astaka, U8/84, Bukit Jelutong Industrial Park, Seksyen U8, 40150 Shah Alam, Selangor.

T +603-7845 3366 **F** +603-7846 9031

Kuala Lumpur +603-7845 3366	Johor Bahru +607-562 5166	Muar +606-951 0386
Ipoh +605-282 6382	Penang +604-530 2417	Sibu +6084-322 022
Bintulu +6086-331 720	Miri +6085-424 716	Kota Kinabalu +6088-218 811
Tawau +6089-776 355	Lahad Datu +6089-886 355	Brunei +673-223 3641
		Sandakan +6089-217 799
		Singapore +65-6353 3933



Ingersoll Rand compressors are not designed, intended or approved for breathing air applications. Ingersoll Rand does not approve specialised equipment for breathing air applications and assumes no responsibility or liability for compressors used for breathing air service.

Nothing contained on these pages is intended to extend any warranty or representation expressed or implied, regarding the product described herein.

Any such warranties or other terms and conditions of sale of products shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request.

Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.